Samsung Medison HS60 Original Ultrasound Sensor LA4-18B Linear Probe

Basic Information

Place of Origin: South KoreaBrand Name: Samsung Medison

Model Number: LA4-18B
Minimum Order Quantity: 1pc
Price: negotiable
Packaging Details: carton
Delivery Time: 3-5 days

Payment Terms: T/T, Western UnionSupply Ability: 10-30pcs/month



Product Specification

Warranty: 60 DaysLead Time: 3-5 DaysService: Outright

 Shipping Method: Express,or As Clients Required
 Highlight: Samsung Medison HS60 Linear Probe, LA4-18B Linear Probe,

Original Ultrasound Sensor Linear Probe



More Images







Product Description

Samsung Medison HS60 Original Ultrasound Sensor LA4-18B Linear Probe

Form Factor: Linear Array Applications: Vascular, Small Parts, Musculoskeletal Frequency Range: 4.0/18.0 Mhz Compatibility: HS60, HS70, HS70A, RS80, RS80A, RS85, WS80A







More details welcome to contact with us!

The Premium Dimension WS80A

The premium dimension in the ultrasound for women's health has opened up with UGEO WS80A, a groundbreaking ultrasound system that provides superior image performance for a variety of women's health exams. With stylish Samsung design and innovative features including the 5D technologies, MPI and ElastoScan™, UGEO WS80A redefines premium ultrasound for women's health.

Dimensions and weight

Height: 1,430 ~ 1,710 mm

Width: 557 mm Depth: 791 ~ 860 mm

Weight with monitor: approx. 105.4 kg (232 lb.)

Power Supply

Voltage: 100- 240 V AC Frequency: 50/60 Hz Power Consumption 714.7 VA with Peripherals 564.7 VA without Peripherals

Nominal Current: 110V: 8.2A 220V: 4.1A

Heat Dissipation: 3207.8BTU/h

Safety Class Ultrasound system: A

Transducer: Depend on transducer specification

Console Design

4 active Probe Ports

Height/Rotate adjustable control panel Height/Tilt/Rotate adjustable monitor

On-board storage for peripherals

6 probe holders

4 Swivel/Lock wheels (wheel diameter: 125 mm)

Front and rear handles

Rear storage cover for peripheral connectors and

cables

Integrated cable management

Integrated high-fidelity stereo speakers Prevention of noise of the system

Easily removable air filter

Integrated SSD 512GB
Integrated DVD Multi Recordable Driver
EMC Class A
Gel Warmer
Endo-cavity Probe holder (Optional)
ECG (Optional)

Touch Screen

10.1" high resolution LED Monitor Display Size: 1280 x 800 Capacitive touch type Virtual Alpha KBD Interactive dynamic soft key menu display Quick Preset for Easy preset change

Monitor

23 inch LCD monitor (LED backlight unit) Resolution: $1920 \times 1080 \times 24$ bits High-Resolution monitor Non Interlace Scan Height: adjustable ~ 270 mm Forth/Back: adjustable ~ 160 mm Tilt: adjustable $+20^{\circ}$ / -15° from center Rotate: adjustable $+/-40^{\circ}$ from center, others $+/-50^{\circ}$ from center High brightness & contrast Digital brightness & contrast adjustment

Operating modes

2D-Mode M-Mode Color-M-Mode Color Doppler Mode Power Doppler Mode S-Flow™ Mode Directional Power Doppler Imaging (DPDI) Pulsed Wave (PW) Spectral Doppler Harmonic Imaging Elastoscan Mode TDI (Tissue Doppler Imaging) Mode TDW (Tissue Doppler Wave) Mode Anatomical M Mode(Arbitary M mode) Single/Dual/Quad mode Volume-mode(3D/4D) Vel+Variance Mode

System Standard Features

Full Spectrum Imaging (3 bands) S-Harmonic Mode Pulse Inversion Harmonic Coded Harmonic Imaging Trapezoidal Imaging Quick Scan™ (Automatic Optimization) ClearVision MultiVision AutoIMT+TM VOCALTM, XI VOCALTM 3D/4D Volume Slice ViewTM Inversion 3D Raw Data Analysis Post-image optimization Patient Information Database Image Archive integrated on CD/DVD and HDD drive Support for external USB 2.0 HDD drive Cine for 12,700(Max Condition) frames and Loop Review for 8,192 lines Auto Calc (Real-Time Automatic Doppler Calculation) Doppler Auto Trace User Configurable Measurement Menu Customizable Measurement Menu Customizable Body Maker Customizable User Keys Post-Measurement On-board electronic documentation

Fully Digital Real Time Recording

Screen Keyboard

5D Cine Beam Steer RMS

Optional Features

4D

3D XI™

3D MXI™

DICOM

DICOM Q/R

XI STIC

Auto IMT+™

Elastoscan

E-Thyroid

E-Breast

Panoramic Imaging

HDVI TM

ADVR TM (Agile DVR)

Mobile Expor

Realistic Vue

5D CNS

5D CNS+

5D Heart

5D Heart Color

5D Follicle

5D NT

5D LB

5D LimbVol.

2D NT

MPI

Smart 4D

S-Detect for Breast

S-Detect for Thyroid

CrystalVue

CrystalVue Flow

IOTA-ADNEX

Biometry Assist

E-Cervix

CEUS +

FOQ:

Q: What is the MOQ?

A: 1pc.

Q: How's the stock condition?

A: Wide variety of Ultrasound probe/board, new&used&compatible new for your choose.

Q: Is there any guarantee for the goods?

A: Fully-tested and safe packing before shipping, less than 3% warranty return claims of previous orders.

Q: Will you provide warranty?

A: Items are sold with NO WARRANTY, unless it is stated otherwise in the body of the proforma invoice/purchase order. Mostly 90 days for new original, 30/60 days for used.

Q: Do you test all your goods before delivery?

A: Yes, we have 100% tested our goods before delivery.

Q: Can I have the goods returned if it is not working good?

A: Yes, goods are permitted to be returned in same received condition within 7 days. Refund will be handled within 2-4 working days after final confirmation (Freight & bank fee excluded). Shipping fee for return should be borne by buyers

Q: If faults occurred after warranty date, can I contact you?

A: Sure, feel free to contact even years later. We'll look into the faults and try to find out some solutions/suggestions for you reference.

Q: How about the payment terms?

A: All orders are 100% prepaid before delivery. We accept wire transfer/ Western Union from bank, and cash. (US dollars, Euro, or CNY)

Q: How about delivery?

A: We ship worldwide. DHL/EMS/FedEx Express will be arranged within 1-5 working days after payment confirmed unless otherwise specified. We Seller are responsible for export Customs clearance in our end, and buyers for import Customs clearance in their end.



+8619536805795

Office 5, 8/F, Mega Cube, 8 Wang Kwong Road, Kowloon Bay, KowLoon, Hong Kong